Application No. 33302 Certificate Record No. 10247 Book 35 10247

## THE STATE OF NEVADA CERTIFICATE OF APPROPRIATION OF WATER

WHEREAS, WILLIAM A. NISDET, Agent	has pro	esented to the State Engineer
f the State of Nevada Proof of Application of Water to Benefic	cials Uses from	***************************************
Indian Creek Spring		***************************************
brough a developed spring and stockwatering t	roughs	
stockwater		***************************************
urposes. The point of diversion of water from the source is a		
R.49E., M.D.B.&M., or at a point from which		
N. 55 <sup>0</sup> 30' W., a distance of 1375.0 feet		
tuated in Eureka County, State of Ne		
Now Know YB, That the State Engineer, under the pro		, has determined the date,
ource, purpose, amount of appropriation, and the place when	e such water is appurter	ant, as follows:
Name of appropriator. Frank Paxton and Fami		
Post-office address Carlin, Nevada		
Amount of appropriation 0.0062 c.f.s., or		
Period of use, from January 1st to		
Date of priority of appropriation. August 23,		
• • • • • • • • • • • • • • • • • • • •		
acceptation of works of diversion, manner and pla	ce or use.	
•		
Spring area consists of a fenced spring with	a 24 inch perfora	ted culvert 7 feet in
Spring area consists of a fenced spring with depth placed into the spring with a 2 inch p	a 24 inch perfora lastic pipe runnin	ted culvert 7 feet in
Spring area consists of a fenced spring with depth placed into the spring with a 2 inch p culvert to a 2 foot by 2 foot by 14 inch hig	a 24 inch-perfora lastic pipe runnin h stockwatering tr	g 100 feet from the
Spring area consists of a fenced spring with depth placed into the spring with a 2 inch p culvert to a 2 foot by 2 foot by 14 inch hig of cattle are watered within the NW% NW% of	a 24 inch perfora lastic pipe runnin h stockwatering tr Section 9, T.24N.,	g 100 feet from the ough where 200 head R.49E., M.D.B.&M.
Spring area consists of a fenced spring with depth placed into the spring with a 2 inch p culvert to a 2 foot by 2 foot by 14 inch hig of cattle are watered within the NW% NW% of	a 24 inch perfora lastic pipe runnin h stockwatering tr Section 9, T.24N.,	g 100 feet from the ough where 200 head R.49E., M.D.B.&M.
Spring area consists of a fenced spring with depth placed into the spring with a 2 inch p culvert to a 2 foot by 2 foot by 14 inch hig of cattle are watered within the NW4 NW4 of	a 24 inch perfora lastic pipe runnin h stockwatering tr Section 9, T.24N.,	g 100 feet from the ough where 200 head R.49E., M.D.B.&M.
Spring area consists of a fenced spring with depth placed into the spring with a 2 inch p culvert to a 2 foot by 2 foot by 14 inch hig of cattle are watered within the NW% NW% of	a 24 inch perfora lastic pipe runnin h stockwatering tr Section 9, T.24N.,	g 100 feet from the ough where 200 head R.49E., M.D.B.&M.
Spring area consists of a fenced spring with depth placed into the spring with a 2 inch p culvert to a 2 foot by 2 foot by 14 inch hig of cattle are watered within the NW% NW% of	a 24 inch perfora lastic pipe runnin h stockwatering tr Section 9, T.24N.,	g 100 feet from the ough where 200 head R.49E., M.D.B.&M.
Spring area consists of a fenced spring with depth placed into the spring with a 2 inch p culvert to a 2 foot by 2 foot by 14 inch hig of cattle are watered within the NW% NW% of	a 24 inch perfora lastic pipe runnin h stockwatering tr Section 9, T.24N.,	g 100 feet from the ough where 200 head R.49E., M.D.B.&M.
Spring area consists of a fenced spring with depth placed into the spring with a 2 inch p culvert to a 2 foot by 2 foot by 14 inch hig of cattle are watered within the NW% NW% of	a 24 inch perfora lastic pipe runnin h stockwatering tr Section 9, T.24N.,	g 100 feet from the ough where 200 head R.49E., M.D.B.&M.
Spring area consists of a fenced spring with depth placed into the spring with a 2 inch p culvert to a 2 foot by 2 foot by 14 inch hig of cattle are watered within the NW% NW% of	a 24 inch perfora lastic pipe runnin h stockwatering tr Section 9, T.24N.,	ted culvert 7 feet in g 100 feet from the ough where 200 head R.49E., M.D.B.&M.
Spring area consists of a fenced spring with depth placed into the spring with a 2 inch p culvert to a 2 foot by 2 foot by 14 inch hig of cattle are watered within the NW% NW% of	a 24 inch perfora lastic pipe runnin h stockwatering tr Section 9, T.24N.,	g 100 feet from the ough where 200 head R.49E., M.D.B.&M.
Spring area consists of a fenced spring with depth placed into the spring with a 2 inch p culvert to a 2 foot by 2 foot by 14 inch hig of cattle are watered within the NW4 NW4 of	a 24 inch perfora lastic pipe runnin h stockwatering tr Section 9, T.24N.,	g 100 feet from the ough where 200 head R.49E., M.D.B.&M.
Spring area consists of a fenced spring with depth placed into the spring with a 2 inch p culvert to a 2 foot by 2 foot by 14 inch hig of cattle are watered within the NW4 NW4 of	a 24 inch perfora lastic pipe runnin h stockwatering tr Section 9, T.24N.,	g 100 feet from the ough where 200 head R.49E., M.D.B.&M.
Spring area consists of a fenced spring with depth placed into the spring with a 2 inch p culvert to a 2 foot by 2 foot by 14 inch hig of cattle are watered within the NW% NW% of This certificate is issued subject to the te	a 24 inch perfora lastic pipe runnin h stockwatering tr Section 9, T.24N., rms of the permit.	ted culvert 7 feet in g 100 feet from the ough where 200 head R.49E., M.D.B.&M.
Spring area consists of a fenced spring with depth placed into the spring with a 2 inch p culvert to a 2 foot by 2 foot by 14 inch hig of cattle are watered within the NW% NW% of This certificate is issued subject to the te	a 24 inch perfora lastic pipe runnin h stockwatering tr Section 9, T.24N., rms of the permit.	ted culvert 7 feet in g 100 feet from the ough where 200 head R.49E., M.D.B.&M.
Spring area consists of a fenced spring with depth placed into the spring with a 2 inch p culvert to a 2 foot by 2 foot by 14 inch hig of cattle are watered within the NW NW of  This certificate is issued subject to the te	a 24 inch perfora lastic pipe runnin h stockwatering tr Section 9, T.24N., rms of the permit.	ted culvert 7 feet in g.100 feet from the ough where 200 head R.49E., M.D.B.&M.
Spring area consists of a fenced spring with depth placed into the spring with a 2 inch p culvert to a 2 foot by 2 foot by 14 inch hig of cattle are watered within the NW\( \) NW\( \) of  This certificate is issued subject to the te  The right to water hereby determined is limited to the ammount above specified, and the use is restricted to the place are in Testimony Whereof, I.	a 24 inch perfora lastic pipe runnin h stockwatering tr Section 9, T.24N., rms of the permit.  ount which can be bracked d for the purpose as set	ted culvert 7 feet in g 100 feet from the ough where 200 head R.49E., M.D.B.&M.  cially used, not to exceed the forth herein.  State Engineer
Spring area consists of a fenced spring with depth placed into the spring with a 2 inch p culvert to a 2 foot by 2 foot by 14 inch hig of cattle are watered within the NW\( \) NW\( \) of  This certificate is issued subject to the te  The right to water hereby determined is limited to the ammount above specified, and the use is restricted to the place are in Testimony Whereof, I.	a 24 inch perfora lastic pipe runnin h stockwatering tr Section 9, T.24N., rms of the permit.  ount which can be benefit d for the purpose as set	g 100 feet from the ough where 200 head R.49E., M.D.B.&M.
Spring area consists of a fenced spring with depth placed into the spring with a 2 inch p culvert to a 2 foot by 2 foot by 14 inch hig of cattle are watered within the NW\( \) NW\( \) of  This certificate is issued subject to the te  The right to water hereby determined is limited to the ammount above specified, and the use is restricted to the place are  In Testimony Whereof, I.	a 24 inch perfora lastic pipe runnin h stockwatering tr Section 9, T.24N., rms of the permit.  ount which can be benefit d for the purpose as set	ted culvert 7 feet in g 100 feet from the ough where 200 head R.49E., M.D.B.&M.  cially used, not to exceed the forth herein.  State Engineer